



THE LOOP™

Hanger for communications cable support. For CAT 5, 6, 7 cable and fiber optic cable.



TL20

TL25



TL50

TL50 holds up to a 5" diameter bundle of CAT 5 or fiber optic cable!

CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	LOOP SIZE	# CAT 5 CABLES	UNIT PKG	STD PKG	DIM A	DIM B	LOAD RATING
TL20	38084	2"	60	100	100	11.375	.652	25
TL25	38085	2-1/2"	100	50	50	12.250	1.500	25
TL50	38086	5"	300	25	25	22.500	5.000	75
TL20P*	38087	2"	60	100	100	11.375	.652	25
TL25P*	38088	2-1/2"	100	50	50	12.250	1.500	25
TL50P*	38089	5"	300	25	25	22.500	5.000	75

*"P" indicates UV Rated.

PATENTED.




See Section M for Beam Clamps

E161207 LR49636

Features and Benefits

- Easy to use...cheaper than trays!
- Flexible and non-metallic
- Holds 2" to 5" diameter bundle of CAT 5 or fiber optic cable — without damaging the cable.
- Available with or without UV rating
- Versatile mounting — rotates to any angle!
- TL25 holds the same amount of cable as a J-hook, at half the cost!



Listed for use in environmental air handling spaces per 2008 NEC code requirements 300-22(c).

1

2

Single Hanger

1. Single LOOP mounted parallel to beam.
2. Single LOOP mounted perpendicular to beam.

(TL50 shown)

3

4

Multiple Hangers

3. Stacked — perpendicular mounting
4. Stacked — parallel mounting

(TL50 shown)